

Data Sheet

VX3R2U8

3 Class 2U 8-Bay Server

Benefit from scalable storage performance and dataset processing with the VX3R2U8 server. This 2U platform brings you scalability and performance to adapt to a variety of video surveillance applications. Up to 196TB of raw storage is provided by up to (8) SATA drives. Paired with the latest Intel® Xeon® Silver 4208 Scalable processor, this provides high density storage with enterprise throughput for the most demanding applications.

Ease of operation is provided with dual OS SSDs for accelerated boot and application load times. Remote management, provided by iDRAC, allows for constant system status and critical resource monitoring. RAID 5/6 storage options, in addition to redundant 1100W/1600W power supplies, provide system high availability while a five-year, on-site, next business day, Keep Your Hard Drive warranty guarantees peace of mind.

KEY FEATURES

- Up to 96TB of Raw Storage
- Intel Silver 4208
- Operating System: Windows 10 Pro / Server 2019
- iDRAC Feature include:
 - Remote Management
 - Disaster Recovery
 - Critical Resource Monitoring



SSD & 24/7 Duty Cycle SATA Drives



5-Year, On-site, NBD



RAID Options: 0, 1, 5, 6 or 10



Redundant Power



Data Sheet

CERTIFIED | PURPOSE BUILT | GUARANTEED

| SYSTEM | |
|------------------------------|---|
| Processor(s) | 1x Silver 4208 |
| Processor Passmark | 11219 |
| Maximim Storage | 96TB |
| Operating System | Windows 10 / Windows Server 2019 |
| OS Drives | 2x 256GB 2.5" SATA SSD |
| Memory | 16GB (2x 8GB) RDIMM ECC |
| RAID | OS RAID 1 |
| RAID Controller | PERC H330 |
| Networking | 4x 1GbE RJ45 Intel i350 rNDC |
| Expansion Slots | 2x PCIe x16 Low-profile |
| Front I/O | 2x USB 2.0, 1x Micro USB for iDRAC |
| Back I/O | 2x USB 3.0, 1x VGA, 1x Serial |
| Remote Management | iDRAC |
| Manufacturer | Dell |
| Warranty | 5-Year, On-site, NBD |
| MECHANICAL | |
| Form Factor | PowerEdge 7920 |
| Rack Support | Yes |
| Hard Drive Bays | 8x 3.5" |
| Hard Drives Supported | Up to 6x 3.5" HDD, 4TB, 8TB, 12TB, 16TB |
| Power Supply(s) | 2x 1100W or 2x 1600W |
| Operating Temperature | 10°C - 35°C |
| Operating Humidity | 10 - 80% |
| Dimensions (WxDxH) | 19" x 29.58" x 3.41" |
| Max. Weight | 61.73lbs |
| Regulatory | IEC 60950-1, European Norm EN 60950-1, CISPR 22/CISPR 24, EN55022/55024 |

